

PRODUCT CODE: EMLITELBK LED RECESSED EMERGENCY LUMINAIRE BLACK FINISH

PRODUCT INFORMATION							
PRODUCT CODE	DESCRIPTION						
EMLITELBK	LED Recessed Emergency Luminaire						
	Black Finish - D40 Classification						

ORDERING INFORMATION								
Carton Qty	10 pieces							
Weight	0.6kg (unit) - 6kg (box)							
Dimension (L x W x H)	228mm x 43mm x 27mm - Control Pack; 84mm(S), 145mm(L) - Head Diameter							



TECHNICAL SPECIFICATIONS								BATTERY AND LEDS								
Operating Mode		Non-Maintained						Battery			High-Temp LiFePO4 Lithium Battery					
Operating Voltage		220-260V; 50Hz							Power Consumption 3W							
Operating Temperature 1° - 45° C							Charging	g Metho	d	3 Stage Intelligence						
IP Rating		IP20						Charging Time			16 Hours					
Wiring		Flex and	Plug				Lens			LED Lamp Rated at 50,000 Hours						
Mounting Type		Recessed Mount						Cutout Size			65mm-80mm(S), 65mm-140mm(L)					
Testing System		Manual	Test Swit													
Construction		Polycark	onate				REPLACEMENT PART									
Classification	co D40 C90 D40							PART N	JMBER		DESCRIPTION					
Standards		AS/NZ 2293						BLITEL			LiFePO4 Lithium Battery, 3.2V 3200mAh					
		AS/NZS 60598.1														
		EMC														
SPACING TABLE AN	ID MC	DUNTING	HEIGHT													
		2.4	2 7	2	3.3m	3.6m	4m	4.5	5m	6m	7m	8m	9m	10m	15m	
CLASSIFICATION 2	2.1m	2.4m	2.7m	3m	3.3111	3.0111	4111	4.5	3111	OIII	/111	om	9111	TOM	13111	

NOTE: Care should be taken when spacing luminaires at the distances indicated by the shaded regions to ensure that conformance to Clause 4.3 of AS/NZS 2293.1 is maintained (e.g. maximum 500 m2 per emergency luminaire).

The product details outlined in this document are accurate as of the document's version date. We reserve the right to modify product design, specifications, or materials without prior notice due to ongoing product improvement policy and changes to industry standards. We recommend confirming the applicable specifications at the time of placing your order to ensure alignment with the most current information







