

PRODUCT CODE: EXBLADELBK ALL-IN-ONE RECESSED BLADE LED BLACK EXIT

PRODUCT INFORMATION		
PRODUCT CODE	DESCRIPTION	
EXBLADELBK	All-in-One Recessed Blade LED Black Exit	
PBLADEBK	Black Adaptor Plate to suit EXBLADELBK	

ORDERING INFORMATION		
Carton Qty	5 pieces	
Weight	1.3kg (unit) - 6.5kg (box)	
Dimension (L x W x H)	365mm x 95mm x 210mm (Overall)	
	365mm x 95mm x 160mm (Recessed)	
	500mm x 150mm x 2mm (Adaptor Plate)	



OPERATIONAL INFORMATION

TECHNICAL SPECIFICATIONS		
Operating Mode	Maintained	
Operating Voltage	220-260V; 50Hz	
Operating Temperature	1° - 45° C	
IP Rating	IP20	
Wiring	Flex and Plug	
Mounting Type	Recessed Mount	
Testing System	Manual Test Switch	
Construction	Polycarbonate Body and Acrylic Diffuser	
Classification	C0 D10 C90 D5	
Standards	AS/NZ 2293	
	AS/NZS 60598.1	
	EMC	

SPACING TABLE AND MOUNTING HEIGHT					
CLASSIFICATION	2.1m	2.4m	2.7m	3m	
D5	7.8	8	8.1	8.2	
D10	10.2	10.5	10.8	11	

BATTERY AND LEDS	
Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	4W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated at 50,000 Hours
Viewing Distance	24 Metres
Cutout	300mm - 360mm x 75mm - 90mm
Adaptor Plate Cutout	300mm - 490mm x 75mm - 140mm

REPLACEMENT PART	
PART NUMBER	DESCRIPTION
BBLADEL	LiFePO4 Lithium Battery, 3.2V 1500mAh

NOTE: This product serves a dual function as both a 24-meter Exit Sign and an Emergency Luminaire, compliant with the following emergency classifications. Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1 2018

The product details outlined in this document are accurate as of the document's version date. We reserve the right to modify product design, specifications, or materials without prior notice due to ongoing product improvement policy and changes to industry standards. We recommend confirming the applicable specifications at the time of placing your order to ensure alignment with the most current information.







