



E&E LIGHTING  
AUSTRALIA

# PRODUCT CODE: EXFIN

## ALL-IN-ONE RECESSED BLADE LED EXIT

### PRODUCT INFORMATION

PRODUCT CODE	DESCRIPTION
EXFIN	All-in-One Recessed Blade LED Exit

### ORDERING INFORMATION

Carton Qty	6 pieces
Weight	2.2kg (unit) - 13.2kg (box)
Dimension (L x W x H)	490mm x 150mm x 195mm



### OPERATIONAL INFORMATION

#### TECHNICAL SPECIFICATIONS

Operating Mode	Maintained
Operating Voltage	220-260V; 50Hz
Operating Temperature	1° - 45° C
IP Rating	IP20
Wiring	Flex and Plug
Mounting Type	Recessed Mount
Testing System	Manual Test Switch
Construction	Polycarbonate Body and Acrylic Diffuser
Classification	C0 D32 C90 D32
Standards	AS/NZ 2293 AS/NZS 60598.1 EMC

#### SPACING TABLE AND MOUNTING HEIGHT

CLASSIFICATION	2.1m	2.4m	2.7m	3m
D32	11.5	13.2	14.8	16.5

#### BATTERY AND LEDS

Battery	High-Temp LiFePO4 Lithium Battery
Power Consumption	4W
Charging Method	3 Stage Intelligence
Charging Time	16 Hours
Lens	LED Lamp Rated at 50,000 Hours
Viewing Distance	24 Metres
Cutout	200mm-480mm x 60mm-120mm

#### REPLACEMENT PART

PART NUMBER	DESCRIPTION
BFIN	LiFePO4 Lithium Battery, 6.4V 1500mAh

NOTE: This product serves a dual function as both a 24-meter Exit Sign and an Emergency Luminaire, compliant with the following emergency classifications. Maximum mounting height allowed is 2.7m but for exceptions see AS2293.1 2018

The product details outlined in this document are accurate as of the document's version date. We reserve the right to modify product design, specifications, or materials without prior notice due to ongoing product improvement policy and changes to industry standards. We recommend confirming the applicable specifications at the time of placing your order to ensure alignment with the most current information.

Version: 0325-02



0487 248 481



[www.eelighting.com.au](http://www.eelighting.com.au)



[sales@eelighting.com.au](mailto:sales@eelighting.com.au)